

EF 4270

Validation and Receipt Printers

UNISYS



The EF 4270 printer series is designed in response to numerous requirements expressed by Unisys customers all over the world.

The EF 4271/EF 4272 printers are particularly outstanding in the following areas:

- Ease of operation*
- Reliability*
- Conservation of space*
- High transaction throughput*
- Ergonomic design*

The EF 4271/EF 4272 printers are compact, highly functional additions to the Unisys family of payment peripherals, expressly designed to validate checks, record transactions on hard copy journal, and dispense excellent quality receipts.

The EF 4270 printer series are an appropriate part of the overall Unisys solution for worldwide financial institutions and public sector agencies or for any organization that requires a cost-effective, specialized form output device, capable of high quality printing.

Benefits and Capabilities

- ▶ High speeds up to 264 characters per inch (cps)
- ▶ Multiple-part, multiple-size document handling
- ▶ Easily replaceable, cost-effective consumables and supplies
- ▶ Independent feeds for validation and receipt/journal operation
- ▶ 5 pitch and front combinations with variable intercharacter spacing

The EF 4270 Printer Series Advantage

- ▶ Intelligent, microprocessor-based 9-wire EF 4271 (without take-up reel) and EF 4272 (with take-up reel) dot matrix printers
- ▶ Bidirectional print speed of 4 lines per second (lps) up to 264 cps
- ▶ Up to 17 lines of validation
- ▶ Autographic window (EF 4272 only)
- ▶ Single RS-232C serial port and one Centronics parallel interface port
- ▶ Selectable baud rates of 300, 600, 1200, 2400, 4800, 9600 and 19200 (communications cables ordered separately)
- ▶ Easily installed 1-ply or 2-ply paper roll
- ▶ Snap-in, high-quality ribbon cartridge (black: 2 M characters, purple: 4 M characters)
- ▶ Multinational character sets including: U.S., U.K., French, Italian, German, Spanish/Latin American and Hebrew
- ▶ Variable vertical line spacing programmable in 1/48ths of an inch
- ▶ Variable horizontal density from 6 to 24 characters per inch (cpi)
- ▶ 16 to 66 characters per line
- ▶ Line graphics and graphics printing capability
- ▶ Ability to handle up to 4-part forms and receipts
- ▶ 32 KB flash memory for downloadable software
- ▶ 7 KB data input buffer
- ▶ EF 4260 downloadable emulation and character sets
- ▶ Low paper and document presence detectors
- ▶ Local or remote control form handling
- ▶ External, autoranging power supply
- ▶ Easily accessible On/Off switch and LED displays

Specifications

Physical Characteristics

| | <u>EF4271</u> | <u>EF4272</u> | <u>Power Supply</u> |
|---------|------------------|------------------|---------------------|
| Height: | 5.6 in (141 mm) | 5.6 in (141 mm) | 2.2 in (59 mm) |
| Width: | 6.4 in (161 mm) | 6.4 in (161 mm) | 6.5 in (165 mm) |
| Depth: | 8.3 in (211 mm) | 11.5 in (293 mm) | 3.2 in (81 mm) |
| Weight: | 5.7 lbs (2.6 kg) | 6.5 lbs (3 kg) | 1.1 lbs (0.5 kg) |
| Color: | Beige | Beige | |

Power Requirements

(line cords ordered separately)

| | |
|--------------|-----------------------------|
| Voltage: | 90 to 264 VAC @ 47 to 63 Hz |
| Noise level: | 60 dbA |

Services

| | |
|--------------|------------------------------------|
| Warranty: | 12 months |
| Service: | Unisys Global Customer Services |
| Maintenance: | No preventive maintenance required |

Approvals and Certifications

| | |
|-----------|-------------------------------|
| Safety: | ETL (Conforms to UL1950, CSA) |
| EMI: | FCC Part 15 Class B |
| European: | CE Certified |

For more information, contact
 Unisys Payment Systems at
<http://www.unisys.com/marketplace/products/psd>

Specifications are subject to change without notice

Unisys is a registered trademark of Unisys Corporation.
 All other brand names and product names are acknowledged to be the service marks, trademarks or registered trademarks of their respective holders.

